

MATERIAL SAFETY DATA SHEET			
Product:	TA-2	<i>Note: The information herein is given in good faith. No warranty, expressed or implied, is made.</i>	
Printed:			
Printed For:			
Original Issue Date:	04/05/90	Approved By:	Chuck Hiddema
Revision No. 5 Date:	05/30/00		V.P. Technical Operations
Section I - Identification			
Manufacturer:	AGS Company		
Street Address:	2651 Hoyt St		
City/State/Zip:	Muskegon Hts., MI 49444		
Phone:	800-253-0403		
Phone:	231-733-2101		
FAX:	231-733-1784		
Transportation Emergency:	CHEM-TEL		
Phone:	800-255-3924		
Trade Name:	Tap-Ease		
Catalog No.:	TA-2		
Common Name:	Tap-Ease		
Container/Size:	Stick,		
NFPA - Health:	0		
Flammability:	1		
Reactivity:	0		
Specific Hazard:			
HMIS - Health:	0		
Flammability:	1		
Reactivity:	0		
Protective Equipment:	A		
Section II - Hazardous Ingredients			
Hazardous Ingredient	CAS No.	Wgt. %	TLV
1 Paraffin Wax	64742-51-4	30-45%	2 cu. M.
2 Petroleum Oil*	Not Assigned	30-45%	5 cu. M.
3 Naphthenic acid, zinc salt	12001-85-3	1-5%	Not Assigned
4			
5			
6			
7			
8			
9			
10			
NOTES:			
*Petroleum oil is severely hydrotreated or solvent refined. It does not require labeling as a carcinogen			

Section III Physical Data		Cat. No. TA-2
pH - Supplied:	Not Determined	
pH - Diluted:	Not Determined	
Water Solubility:	Insoluble	
Specific Gravity:	(Water=1) 0.75	
Melting Point:	162 F. ASTM D127	
Boiling Point:	Not Determined	
% Volatiles:	Nil	
Vapor Pressure:	Negligible	
Vapor Density:	N/A	
Evaporation Rate:	N/A	
Appearance:	Tan waxy solid with bland petroleum odor.	
Section IV Fire & Explosion Data		
Flash Point:	380 F	
Method:	C.O.C.	
Auto Ignition Temperature:	Not Determined	
Flammable Limits in Air	LEL: Not Determined	
	UEL: Not Determined	
Extinguishing Media:	Dry chemical, foam, carbon dioxide or water fog.	
Special Procedures:	Wear self-contained breathing apparatus. Use water fog to minimize vapors in air.	
Unusual Hazards:	None	
Section V - Reactivity Data		
Unstable and/or Auto Reactive:	Stable	
Incompatible Materials:	Strong Oxidizers	
Hazardous Decomposition Products:	Oxides of carbon and zinc.	
Section VI - Emergency First Aid		
Eyes:	Flush with water for at least 15 minutes. Consult a physician.	
Skin:	Wash with soap and water. Get medical attention if adverse effects arise.	
Ingestion:	Do not induce vomiting. Consult a physician.	
Inhalation:	Remove to fresh air. Administer oxygen or artificial respiration as needed.	
Section VII - Health Effects		
Eyes:	May cause irritation.	
Skin:	In molten state may cause burn.	
Ingestion:	Not known.	
Inhalation:	Aspiration or inhalation of fumes or mist may cause respiratory problems.	
Other Effects:	Not known.	

Section VIII - Ventilation and Protective Measures		Cat. No. TA-2
Ventilation Requirement:	Local exhaust when using product in molten state.	
Eyes:	Yes	
Gloves:	Yes	
Clothing:	No	
Respiratory:	Yes	
Other:	Eye wash in work area.	
Section IX - Storage and Handling Procedures		
Conditions to Avoid:	Avoid excess heat and ignition sources	
Section X - Spill Procedures and Waste Disposal		
Spill Procedure:	Dike area to contain product spill. Allow to cool, scrape material up and place in container for disposal.	
Disposal Method:	Removal by an approved licensed waste hauler.	
EPA Waste I.D. NO.:	Not Reg.	