

— Section 1 —  
Product Identification



The Sherwin-Williams Company  
Krylon Products Group  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

Emergency telephone numbers (216) 566-2917 United States  
Information telephone number (800) 251-2486  
July 10, 2000 @2000, The Sherwin-Williams Co.

# Material Safety Data Sheet

## RUST TOUGH® Aerosol Paints - Fluorescents

RT5/KRI

CAS No.	Section 2 — Hazardous Ingredients (percent by weight)	ACGIH TLV		OSHA PEL		Vapor Pressure (mm Hg)	R10339 Fluorescent Green	R10429 Fluorescent Yellow	R10559 Fluorescent Orange	R10649 Fluorescent Red
		<STEL>	<STEL>	<STEL>	<STEL>					
74-98-6	Propane	2500	1000	PPM	760.0	13	13	13	13	
106-97-8	Butane	800	800	PPM	760.0	12	12	12	12	
110-54-3	Hexane	50	50	PPM	127.0	1	1	1	1	
64742-89-8	V. M. & P. Naphtha.	300	300	PPM	12.0	9	9	9	9	
100-41-4	§ Ethylbenzene	100	100	PPM	7.1	2	2	2	2	
1330-20-7	§ Xylene.	<125>	<125>	PPM	5.9	12	12	12	12	
67-64-1	Acetone.	100	100	PPM	5.9	12	12	12	12	
471-34-1	Calcium Carbonate.	500	1000	PPM	180.0	15	15	15	15	
	Weight per Gallon (lbs.)	10	10 [5]	Mg/M3 as Dust [Resp. Fraction]		17	17	17	17	
	VOC Less Water & Federally Exempt Solvents (percent by weight)					6.99	6.97	6.97	6.97	
	Flash Point (°F)					50.8	51.2	51.2	51.2	
	HMIS (NFPA) Rating (Health - Flammability - reactivity)					<0	<0	<0	<0	

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

%  
B  
Y  
W  
F  
I  
G  
H  
T

# RUST TOUGH® Aerosol Paints & Primers

RT5/KRI

## Section 3 — Physical Data

PRODUCT WEIGHT	See TABLE	EVAPORATION RATE	Faster than Ether
SPECTIC GRAVITY	0.75-1.08	VAPOR DENSITY	Heavier than Air
BOILING RANGE	<0 - 395 °F	MELTING POINT	N.A.
VOLATILE VOLUME	>80 %	SOLUBILITY IN WATER	N.A.

## Section 4 — Fire And Explosion Hazard Data

FLASH POINT	See TABLE	LET	0.9	UEL	12.8
EXTINGUISHING MEDIA	Carbon dioxide, Dry Chemical, Foam				

**UNUSUAL FIRE AND EXPLOSION HAZARDS**  
Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**  
Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## Section 5 — Health Hazard Data

**ROUTES OF EXPOSURE**  
Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

**ACUTE Health Hazards**  
**EFFECTS OF OVEREXPOSURE**  
Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

**R00179 contains Cadmium.** Overexposure to Cadmium may result in kidney damage.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**  
Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

**Redness and itching or burning sensation may indicate eye or excessive skin exposure.**

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**  
None generally recognized.

**EMERGENCY AND FIRST AID PROCEDURES**  
**IF INHALED:** If affected, remove from exposure. Restore breathing. Keep warm and quiet. Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

**IF IN EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention. Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITTING.

**IF ON SKIN:** Wash affected area thoroughly with soap and water. Seek medical attention.

**CHRONIC Health Hazards**  
Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Carbon Black is classified by IARC as possibly carcinogenic to humans (Group 2B) based on experimental animals data, however, there is inadequate evidence in humans for its carcinogenicity.

Cobalt and cobalt compounds are classified by IARC as possibly carcinogenic to humans (Group 2B) based on experimental animals data, however, there is inadequate evidence in humans for its carcinogenicity.

Prolonged and repeated exposure to Hexane may cause damage to nerve tissue of the arms and legs (peripheral neuropathy), resulting in muscular weakness and loss of sensation. This effect may be increased by the presence of Methyl Ethyl Ketone.

Prolonged overexposure to solvent ingredients in R00859, R100429, R10959, R10649 may cause adverse effects to the liver, urinary, and reproductive systems. Prolonged overexposure to solvent ingredients in all other listed products may cause adverse effects to the liver, urinary, cardiovascular, and reproductive systems.

Methyl Ethyl Ketone may increase the nervous system effects of other solvents.

Rats exposed to titanium dioxide dust at 250 mg./m<sup>3</sup> developed lung cancer, however, such exposure levels are not attainable in the workplace.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

## Section 6 — Reactivity Data

**STABILITY** — Stable  
**CONDITIONS TO AVOID** — None known.  
**INCOMPATIBILITY** — None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**  
By fire: Carbon dioxide, Carbon Monoxide, Oxides of Metals in Section 2.  
**HAZARDOUS POLYMERIZATION** — Will Not Occur

## Section 7 — Spill Or Leak Procedures

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**  
Remove all sources of ignition. Ventilate and remove with inert absorbent.

**WASTE DISPOSAL METHOD**  
Waste from these products may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Waste from products containing Methyl Ethyl Ketone may also require extractability testing.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and local regulations regarding pollution.

## Section 8 — Protection Information

**PRECAUTIONS TO BE TAKEN IN USE**  
R00179 contains Cadmium. Before initial use, consult OSHA's Standard for Occupational Exposure to Cadmium (29 CFR 1910.1027).

Use all products only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These products may contain materials classified as nuisance particulates (listed "as dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m<sup>3</sup> (total dust), 3 mg./m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg./m<sup>3</sup> (total dust), 5 mg./m<sup>3</sup> (respirable fraction).

**VENTILATION**  
Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**  
If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**  
None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

**EYE PROTECTION**  
Wear safety spectacles with unperforated side shields.

## Section 9 — Precautions

**DOZ STORAGE CATEGORY - 1A**  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**  
Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

during use and until all vapors are gone: Keep area ventilated. Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120°F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

**OTHER PRECAUTIONS**  
Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

## Section 10 — Other Regulatory Information

**CALIFORNIA PROPOSITION 65**  
**WARNING:** These products contain chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm.

**TSCA CERTIFICATION**  
All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.