

MATERIAL SAFETY DATA SHEET

1316
01 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

1316

HMIS CODES

Health 2
Flammability 4
Reactivity 0

PRODUCT NAME

KRYLON* Sandable Primer, Charcoal Black

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
KRYLON Products Group
Cleveland, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917

DATE OF PREPARATION

28-DEC-01

INFORMATION TELEPHONE NO.
(800) 832-2541

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
17	74-98-6	Propane		
		ACGIH TLV	2500 ppm	760 mm
		OSHA PEL	1000 ppm	
5	64742-89-8	V. M. & P. Naphtha.		
		ACGIH TLV	300 ppm	12 mm
		OSHA PEL	300 ppm	
		OSHA PEL	400 ppm STEL	
25	108-88-3	Toluene.		
		ACGIH TLV	50 ppm (skin)	22 mm
		OSHA PEL	100 ppm (skin)	
		OSHA PEL	150 ppm (skin) STEL	
2	78-83-1	2-Methyl-1-propanol		
		ACGIH TLV	50 ppm	8.7 mm
		OSHA PEL	50 ppm	
33	67-64-1	Acetone.		
		ACGIH TLV	500 ppm	180 mm
		ACGIH TLV	750 ppm STEL	
		OSHA PEL	1000 ppm	
7	14807-96-6	Talc		
		ACGIH TLV	2 mg/m3 as Resp. Dust	
		OSHA PEL	2 mg/m3 as Resp. Dust	

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

Continued on page 2

KD-1316

=====

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

=====

Section 4 -- FIRST AID MEASURES

- If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
- If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.
- If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- If SWALLOWED: Do not induce vomiting. Get medical attention immediately.
- =====

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL
Propellant < 0 F	0.9	12.8

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

=====

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

=====

Section 7 -- HANDLING AND STORAGE

DOL STORAGE CATEGORY

1A

=====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

=====

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

=====
 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT 6.74 lb/gal 807 g/l
 SPECIFIC GRAVITY 0.81
 BOILING POINT <0 - 325 F <-18 - 162 C
 MELTING POINT Not Available
 VOLATILE VOLUME 91 %
 EVAPORATION RATE Faster than ether
 VAPOR DENSITY Heavier than air
 SOLUBILITY IN WATER N.A.
 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)
 Volatile Weight 48.97 % Less Federally Exempt Solvents
 HMIS -- 2 4 0

 =====
 Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable
 CONDITIONS TO AVOID
 None known.
 INCOMPATIBILITY
 None known.
 HAZARDOUS DECOMPOSITION PRODUCTS
 By fire: Carbon Dioxide, Carbon Monoxide
 HAZARDOUS POLYMERIZATION
 Will not occur

 =====
 Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.
 Prolonged overexposure to solvent ingredients in Section 2 may cause
 adverse effects to the liver, urinary, cardiovascular and reproductive
 systems.

Reports have associated repeated and prolonged overexposure to solvents
 with permanent brain and nervous system damage.

 TOXICOLOGY DATA

CAS No.	Ingredient Name				
74-98-6	Propane	LC50	RAT	4HR	Not Established
		LD50	RAT		Not Established
64742-89-8	V. M. & P. Naphtha.	LC50	RAT	4HR	Not Established
		LD50	RAT		Not Established
108-88-3	Toluene.	LC50	RAT	4HR	4000 ppm
		LD50	RAT		5000 mg/kg
78-83-1	2-Methyl-1-propanol	LC50	RAT	4HR	Not Established
		LD50	RAT		2460 mg/kg
67-64-1	Acetone.	LC50	RAT	4HR	Not Established
		LD50	RAT		5800 mg/kg

Continued on page 5

14807-96-6

Talc

LC50
LD50

RAT
RAT

4HR

Not Established
Not Established

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION
No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

No data available.

Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
108-88-3	Toluene.	25	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.