



The Precision Color Company

P.O. Box 1090 - Menomonee Falls, WI 53052-1090
N92 W14701 Anthony Ave. - Menomonee Falls, WI 53051-1630
800-768-7580 - 414-255-9508 - Fax 414-255-0684

80810

DLB

PAGE 2

MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE . . . : 07524 051208 604
PRODUCT NAME . . . : BROWN WRINKLE
PRODUCT CLASS . . . : Aerosol Touch-Up

MSDS PREPARATION DATE : 02/16/2000

MANUFACTURER IDENTIFICATION:

RAABE CORPORATION
PO BOX 1090

CUSTOMER IDENTIFICATION:

Kennedy Manufacturing Company
P.O. Box 151

MENOMONEE FALLS WI 53052

Van Wert,

OH 45891-0151

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 CARBON BLACK

CAS# 1333-86-4
CARBON BLACK
PCT BY WT: .2300

LEL 99.00

EXPOSURE LIMIT:

ACGIH TLV-TWA 3.5 mg/M3
ACGIH TLV-STEL NO INFO

2 ETHYL BENZENE

CAS# 100-41-4
ETHYL BENZENE
PCT BY WT: 2.0000

LEL 1.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm
ACGIH TLV-STEL 125 ppm

3 N-BUTANE

CAS# 106-97-8
N-BUTANE

PCT BY WT: 6.0000 VAPOR PRESSURE: 879.100 MMHG @ 68F LEL 1.80

EXPOSURE LIMIT:

ACGIH TLV-TWA 800 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 800 ppm
COMPANY N.E.

4 PROPANE

07524 051208 604 RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

CAS# 74-98-6

PROPANE

PCT BY WT: 18.0000 VAPOR PRESSURE: 5585.200 MMHG @ 68F LEL 2.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 1000 ppm
ACGIH TLV-STEL NO INFORMATION

5 AMORPHOUS PRECIPITATED SILICA

CAS# 112926-00-8

AMORPHOUS PRECIPITATED SILICA

PCT BY WT: 1.0000

EXPOSURE LIMIT:

ACGIH TLV-TWA 10 mg/m3
ACGIH TLV-STEL NO INFO

6 XYLENE

CAS# 1330-20-7

XYLENE

PCT BY WT: 9.0000 LEL 1.00

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm
ACGIH TLV-STEL 150 ppm
OSHA PEL-TWA 100 ppm
COMPANY N.E.

7 ACETONE

CAS# 67-64-1

ACETONE

PCT BY WT: 37.0000 VAPOR PRESSURE: 185.000 MMHG @ 68F LEL 2.60

EXPOSURE LIMIT:

ACGIH TLV-TWA 750 ppm
ACGIH TLV-STEL 1000 ppm
OSHA PEL-TWA 750 ppm
OSHA PEL-STEL 1000 ppm
COMPANY N.E.

8

CAS# 108-65-6

PROPYLENE GLYCOL METHYL ETHER ACETATE

PCT BY WT: 6.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30

EXPOSURE LIMIT:

ACGIH TLV-TWA NOT ESTABLISHED
ACGIH TLV-STEL NOT ESTABLISHED

9 TOLUENE

CAS# 108-88-3

TOLUENE

PCT BY WT: 2.0000 VAPOR PRESSURE: 38.000 MMHG @ 68F LEL 1.40

EXPOSURE LIMIT:

ACGIH TLV-TWA 50 ppm

07524 051208 604

RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 50 ppm
COMPANY N.E.

This product contains one or more reported carcinogens or suspected carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits recommended column.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

- Harmful if swallowed.
- Harmful if inhaled.
- Causes eye irritation.
- Causes skin irritation.
- Vapors irritating to eyes and respiratory tract.
- Extremely flammable liquid and vapor.
- Vapors may cause flash fire or explosion.
- Extremely flammable aerosol.
- Contents under pressure.

POTENTIAL HEALTH EFFECTS:

EYE:

May cause severe eye irritation.

SKIN:

May cause skin irritation.
Repeated and prolonged contact with the skin may cause allergic dermatitis.

INHALATION:

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.
Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.
Liquid or vapor may be irritating to skin, eyes, throat or lungs.
Prolonged inhalation of dusts containing free silica may result in the development of a disabling pulmonary fibrosis(lung disease) known as silicosis.
Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.
Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:
Kidney damage

07524 051208 604

RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

- Eye damage
- Lung damage
- Liver damage
- Spleen damage
- Anemia
- Brain damage

Chronic overexposure to a component or components is this product has been suggested as a cause of the following effects in humans:

- Liver damage
- Cardiac abnormalities

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Product contains toluene which may be harmful to the fetus based on animal studies.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

In April 1996, The International Agency for Research on Cancer (IARC) published Monograph 65 which reclassifies Carbon Black into Group 2B (possibly carcinogenic to humans).

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

Flush with large quantities of water for 15 minutes.

SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

NOTE TO PHYSICIAN:

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint	: Less Than -25 °F
Explosion Level	: Low - 1.0
	: High - 100.0
Flammability Limits	: Lower - -N/A
	: Higher - -N/A

EXTINGUISHING MEDIA:

07524 051208 604
RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

Use Dry Chemical, Carbon Dioxide or Chemical Foam.
FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Contents under pressure. Do not use or store near sources of heat, sparks or open flame. Keep away from any source of heat such as sunlight, heaters or stoves that could cause the container to burst. Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat.

Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back.

Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.

Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.

Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbant materials and non-sparking tools.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Wash hands thoroughly after handling.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or

07524 051208 604 RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

repeated contact.
EYE PROTECTION:
Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.
OTHER PROTECTIVE EQUIPMENT:
Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.
HYGIENIC PRACTICES:
Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure : 5585.20 mm Hg @ 20 C
Vapor Density : -N/A
Boiling Range : Lower - 1.0 °F
Higher - 999.0 °F
Specific Gravity : .765
Formula Weight per Volume : 6.3725 LB/GL
VOC (Calculated, LB/GAL) : 4.331
VOC (Calculated, GM/L) : 518.98
Percent Volatile by Weight : 81.3109
Evaporation Rate : 7.700 (n-Butyl Acetate = 1)
Viscosity : -N/A

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:
Avoid contact with heat, sparks, and open flame.
Product may explode if heated. Keep cool, avoid exposure to heat.
INCOMPATIBILITIES:
Strong oxidizing agents.
DECOMPOSITION:
Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.
POLYMERIZATION:
No hazardous polymerization will occur under normal conditions.
STABILITY:
The product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 3 for available information on potential health effects.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

07524 051208 604 RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Domestic ground shipment of Paint Aerosols and all liquid paint products in Containers of 1 Quart or less: CONSUMER COMMODITY, ORM-D

Domestic air shipment of Paint Aerosols and all liquid paint in containers of 1 quart or less: CONSUMER COMMODITY, CLASS 9, ID 8000, MISCELLANEOUS LABEL

International Air Shipments of Paint Aerosols: AEROSOLS, FLAMMABLE, N.O.S. CLASS 2.1, UN 1950, FLAMMABLE GAS LABEL

International Air Shipment of liquid paint in containers of 1 quart or less: PAINT, CLASS 3, UN 1263, FLAMMABLE LIQUID LABEL

All shipments of Liquid Paint in containers of more than 1 quart: PAINT, CLASS 3, UN 1263, PACKING GROUP II, FLAMMABLE LIQUID LABEL

See 49 CFR 172.101, Hazardous Materials Table 1 for more information on shipping hazardous materials on land.
See IATA Dangerous Goods Regulations for more details on shipping hazardous materials by air.

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

ETHYL BENZENE
CAS# 100-41-4 PCT BY WT: 2.1770

XYLENE
CAS# 1330-20-7 PCT BY WT: 9.4320

TOLUENE
CAS# 108-88-3 PCT BY WT: 1.9480

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are

07524 051208 604 RAABE CORPORATION
MATERIAL SAFETY DATA SHEET
01

listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California the following warning statement must appear on the label:

Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

No non-hazardous ingredients are among the top five ingredients

PENNSYLVANIA RIGHT-TO-KNOW

No non-hazardous ingredients are present greater than 3%

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS:

HEALTH: 2* FLAMMABILITY: 4 REACTIVITY: 0 PERSONAL PROTECTION: G