

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: NU GLO LT SCRATCH REMOVER (~~FINISH~~ FINISH PRESERVER) HMTS CODES: H F R P
 PRODUCT CODE: M840-400 M840B 1 3 0 B

=====SECTION I - MANUFACTURER IDENTIFICATION=====

MANUFACTURER'S NAME: Mohawk Finishing Products, Inc.

ADDRESS : 4715 State Hwy 30
 Amsterdam, New York 12010

GENERAL ID : OIL FINISH EMERGENCY PHONE: 518-843-1380

DOT HAZARD CL. : FLAMMABLE LIQ. (3) INFORMATION : 518-843-1380

PACKING GRP. : II DATE PRINTED: 10/14/98

UN/NA#/ERG : UN 1263 G 127 SIGNATURE OF PREPARER : *[Signature]*

=====SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION=====

REPORTABLE COMPONENTS	CAS NUMBER	%	OSHA PEL	ACGIH/TLV	MG/M3
* TOLUENE	108-88-3	23	100 PPM	100 PPM	375
* XYLENE	1330-20-7	9	100 PPM	100 PPM	434
MINERAL SPIRITS	MIXTURE	>1	400 PPM	100 PPM	525

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

=====SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS=====

BOILING PT. : 230F/110C SPECIFIC GRAVITY (Approx.) : 0.89
 VAPOR PRES. : 38 MM EVAPORATION RATE: <1.0 (B. Acetate=1)
 VAPOR DENSITY: >1.0 (AIR=1) MATL. VOC : 319 g/l 2.66 lb/gl
 SOLUBILITY IN WATER: Negligible. HAP/LB SOLIDS: 0.50
 APPEARANCE AND ODOR: Dark liquid, aromatic odor. MELTING PT: N/A

=====SECTION IV - FIRE AND EXPLOSION HAZARD DATA=====

FLASH PT. : 45F/7.22C METHOD USED: TCC
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.0% UPPER: 13.3%
 EXTINGUISHING MEDIA: Water spray, "alcohol" foam, dry chemical, foam, CO2, or any class B extinguishing agent.
 SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting fires in confined space. If water is used, fog nozzles are preferred.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air, may travel considerable distance to a source of ignition and flashback. Use water fog to cool containers to prevent rupturing.

=====SECTION V - REACTIVITY DATA=====

STABILITY: Yes CONDITIONS TO AVOID: N/A.
 INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing materials can cause a vigorous reaction.
 HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Combustion will produce fumes, smoke, carbon dioxide, and probably carbon monoxide.
 HAZARDOUS POLYMERIZATION: Will not occur.

=====SECTION VI - HEALTH HAZARD DATA=====

HEALTH HAZARDS (ACUTE AND CHRONIC): Harmful if inhaled, may affect the brain or nervous system, causing dizziness, headache or nausea. Causes nose, throat, eye and skin irritation. Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

MUTAGENICITY: No NTP CARCINOGEN: N/L.
 IARC MONOGRAPHS: N/L. OSHA REGULATED: N/L.
 SUBJECT TO CA. PROPOSITION 65 REPORTING? CARCINOGEN: NO REPRODUCTIVE: YES

ADVERSE AND SYMPTOMS OF EXPOSURE:
 Breathing difficulty, light-headedness, dryness of respiratory tract.
 MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Any medical condition,

MATERIAL SAFETY DATA SHEET

allergy, sensitization which may become worse upon exposure to the product.

EMERGENCY AND FIRST AID PROCEDURES: IN EYES: Flush immediately with large amounts of water for 15 minutes. Take to physician for treatment. IF INHALED: Remove to fresh air, restore breathing. Consult a physician. IF ON SKIN: Wash areas with soap and water. Remove contaminated clothing. Consult physician. IF SWALLOWED: Do not induce vomiting. Consult physician immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Isolate, absorb and ventilate (open all windows, doors). Removal of all ignition sources, flames, hot surfaces. Avoid breathing of vapors, use respiratory protective device.

WASTE DISPOSAL METHOD:

In accordance with federal, state and local regulations. Before attempting clean-up, refer to hazard caution information in other sections of form.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Avoid high temperatures. Do not store or use near heat, sparks or flame.

Prevent prolonged or repeated breathing of vapor or spray mist.

OTHER PRECAUTIONS: Do not take internally. Avoid prolonged contact with skin.

DO NOT GET IN EYES. Avoid breathing of vapors or dust. **KEEP OUT OF REACH OF CHILDREN!** Follow label directions.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION: If workplace exposure limit(s) of product or any component is exceeded, a NIOSH approved, organic vapor cartridge respirator is advised in absence of proper environmental control.

VENTILATION

LOCAL : Local exhaust not adequate.

MECHANICAL : Mechanical exhaust sufficient to prevent exceeding listed TLV.

When unavailable, supplied air respiratory protection is recommended.

PROTECTIVE GLOVES: Neoprene gloves.

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other types of safety glasses. Consult your safety representative.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: N/A.

WORK/HYGIENIC PRACTICES: Personal contact should be avoided. Follow good housekeeping and personal hygiene.

===== SECTION IX - DISCLAIMER =====

To the best of our knowledge the information contained herein is accurate. All information has been obtained from sources which Mohawk Finishing Products, Inc. believes to be accurate.