

Latex Dipped Glove Product Sheet











GL501C5

HPPE | Latex | Crinkle

ANSI/ISEA 105-2016 - CUT A4 | ABRASION 4 EN388: 2016 - 3X42D

Latex crinkle palm coating // 13 gauge HPPE liner // Good grip in all conditions

GL501C5 S - 2XL

Suggested Applications

Material Handling // Glass Handling // General Maintenance // Wood Working // Recycling + Sanitation Operations

Glove Breakdown

Type: Dipped Glove	
Material: Latex Crinkle	
Liner: 13 Gauge HPPE	
Cuff: HPPE + Latex Elastic	

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

FN388-2016 - 3X42D

ENGGG. EGEG GX IEB						
Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	Α	В	С	D	Ε	F
Impact Rated	Р	F				

ANSI/ISEA 105-2016

741017 10274 200 2020									
Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				

Pyramex gloves that comply with the EN388:2003 standard can still be sold. As we move forward, we will start testing to the current 2016standard.



Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of

Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China