

# GL604C5

HPPE | Nitrile | Sandy

ANSI/ISEA 105-2016 – CUT A4 | ABRASION 6  
EN388: 2016 – 4X43D

Nitrile sandy palm coating // 13 gauge HPPE liner //  
Good grip in all conditions // Extra absorption

GL604C5 S – 2XL

### Suggested Applications

Assembly Line // Furniture Manufacturer // HVAC //  
Aerospace // Handling Oily Parts // Construction

### Glove Breakdown

Type: Dipped Glove
Material: Nitrile Sandy
Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic

This product contains components that may be a potential risk to allergic reactions [latex in the wrist cuff]. Do not use in the event of hypersensitivity signs or a known allergy to latex.

### Testing Performance

EN388: 2016 – 4X43D

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			

ANSI/ISEA 105-2016

Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				

Pyramex gloves that comply with the EN388:2003 standard can still be sold. As we move forward, we will start testing to the current 2016 standard.



Nitrile



Abrasion



Cut



Tear



Puncture



### Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

### Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China